



■■■■■
**PHENTEX CHUNKY
 HOODED SWEATSHIRT
 TO CROCHET**

SIZES: To fit bust measurement:
 XS/S (M-L-XL-2/3XL-4/5XL): 28/34
 (36/38-40/42-44/46-48/54-56/62)
 ins [71/86.5 (91.5/96.5-101.5/106.5-
 112/117-122/137-142/157.5) cm].

Finished bust: 38 (42-46-50-60-68) ins
 [96.5 (106.5-117-127-152.5-173) cm].

MATERIALS: Phentex Chunky
 (Ombres: 300 g/10.5 oz)
 3 (3-3-4-4-4) balls

Size 6 mm (U.S. J or 10) crochet hook **or**
size needed to obtain gauge.

GAUGE
 14 sts and 16 rows = 4 ins [10 cm] in pat.

ABBREVIATIONS
www.bernat.com/glossary.php

INSTRUCTIONS: *The instructions are written for smallest size. If changes are necessary for larger sizes the instructions will be written thus ().*

BACK
 **Ch 68 (74-82-88-106-120).
1st row: (RS). 1 sc in 2nd ch from hook.
 *Ch 1. Miss next ch. 1 sc in next ch. Rep
 from * to end of ch. Turn. 67 (73-81-87-
 105-119) sts.
2nd row: Ch 1. 1 sc in first sc. 1 sc in
 next ch-1 sp. *Ch 1. 1 sc in next ch-1 sp.
 Rep from * to last sc. 1 sc in last sc. Turn.
3rd row: Ch 1. 1 sc in first sc. *Ch 1. 1 sc
 in next ch-1 sp. Rep from * to last sc. 1 sc
 in last sc. Turn.
 Rep last 2 rows of pat for 5 ins [12.5 cm],
 ending with 3rd row. Place marker at each
 end of last row.

Cont in pat for total length of 15 ins
 [38 cm], ending with 2nd row. Fasten off.

Shape armholes: Next row: (RS). Miss
 first 8 (8-10-12-20-26) sts. Join yarn
 with sl st in next ch-1 sp. Ch 1. 1 sc in
 same sp as last sl st. Pat to last 8 (8-10-
 12-20-26) sts. **Turn.** Leave rem sts
 unworked. 51 (57-61-63-65-67) sts.**

Cont even in pat until armholes measure
 9 (9½-10-10½-11-12) ins [23 (24-25.5-
 26.5-28-30.5) cm], ending with a 2nd
 row. Fasten off.

FRONT
 Work from ** to ** as given for Back.
 Cont even in pat until armholes measure
 3 ins [7.5 cm], ending with a 2nd row.

Divide for front opening: Next row:
 Pat across 25 (28-30-31-32-33) sts.
Turn. Leave rem sts unworked.
 Cont even until armhole measures 12
 rows less than Back to shoulder, ending
 with a 2nd row.

Shape neck: Next row: (RS). Pat across
 20 (22-23-23-24-24) sts. *Draw up a
 loop in each of next 2 sts. Yoh and draw
 through all 3 loops on hook - sc2tog*
 made. Turn. 21 (23-24-24-25-25) sts.

Next row: Ch 1. Sc2tog over first 2 sts.
 Pat to end of row. Turn.

Next row: Ch 1. Pat to last 2 sts. Sc2tog
 over last 2 sts. Turn.
 Rep last 2 rows once more. 17 (19-20-
 20-21-21) sts.

Next row: Ch 1. Pat to end of row. Turn.
Next row: Ch 1. Pat to last 2 sts. Sc2tog
 over last 2 sts. Turn.

Rep last 2 rows twice more. 14 (16-17-
 17-18-18) sts.
 Work 1 row even. Fasten off.

With RS of work facing, miss center st.
 Join yarn with sl st to next st and pat to
 end of row.

Work as given for left side, reversing neck
 shaping.

SLEEVES
 Ch 36 (36-38-38-40-42).
 Proceed in pat as given for Back for 4
 rows. 35 (35-37-37-39-41) sts.
Next row: (RS). (Increase row). Ch 1. 2
 sc in first st. Pat to last st. 2 sc in last st.
 Turn.
 Work 3 (3-2-2-2-2) rows even.
 Rep last 4 (4-3-3-3-3) rows 12 (14-15-
 16-17-19) times more, then Increase row
 once. 63 (67-71-73-77-83) sts.

Cont even until work from beg measures
 17½ (18-18-17½-17-16½) ins [44.5
 (45.5-45.5-44.5-43-42) cm], ending
 with 2nd row. Place marker at each end
 of last row.
 Work 9 (9-11-14-23-30) rows even.
 Fasten off.

HOOD
 Ch 98.
 Proceed in pat as given for Back for 4 (5-
 6-7-7-8) rows. 97 sts.

Next 5 rows: Ch 1. Sc2tog over first
 2 sts. Pat to last 2 sts. Sc2tog over last
 2 sts. Turn.

Next row: Ch 1. Pat to end of row. Turn.
Next 3 rows: Ch 1. Sc2tog over first
 2 sts. Pat to last 2 sts. Sc2tog over last 2
 sts. Turn. 81 sts at end of last row.

Work 13 (14-15-17-17-18) rows even.
 Place marker at each end of last row.

Shape back: Next 8 rows: Sl st in each
 of first 3 sts. Pat to last 3 sts. **Turn.** Leave
 rem sts unworked. 33 sts at end of last
 row. Fasten off.

Fold Hood in half, matching markers. Sew
 back seam from fold to markers.

FINISHING
 Sew shoulder seams. Sew in Sleeves,
 placing rows above markers against
 missed sts of Front and Back to form
 square armholes. Sew side and sleeve
 seams, leaving sides open below markers
 for side slits. Pin Hood to neck edge,
 aligning back seam with center back neck
 and foundation ch with edges of front
 opening. Sew Hood in position.



*Make the best for less
 L'art de faire pour moins cher*